

**COAXIAL CONNECTOR HAVING DETACHABLE LOCKING SLEEVE**

This application claims priority to U.S. provisional application No. 60/202,972, filed on May 10, 2000, and U.S. provisional application No. 60/215,299 filed on June 30, 2000.

5

**FIELD OF THE INVENTION:**

The present invention relates generally to connectors for terminating coaxial cable. More particularly, the present invention relates to a coaxial cable connector having a locking sleeve which is detachably coupled to the connector body.

**BACKGROUND OF THE INVENTION:**

It has long been known to use connectors to terminate coaxial cable so as to connect a cable to various electronic devices such as televisions, radios and the like.

Conventional coaxial cables typically include a center conductor surrounded by an insulator. A braided or foil conductive shield is disposed over the insulator. An outer insulative jacket surrounds the shield. In order to prepare the coaxial cable for termination, the outer jacket is stripped back exposing an extent of the conductive shield which is folded back over the jacket. A portion of the insulator extends outwardly from the jacket and an extent of the center conductor extends outwardly from insulator. Such a prepared cable may be terminated in a conventional coaxial connector.

15

20

Coaxial connectors of this type include a connector body having an inner cylindrical post which is inserted between the insulator and the conductive shield. A locking sleeve is provided to secure the cable within the body of the coaxial connector. The locking sleeve, which is typically formed of a resilient plastic, is securable to the connector body to secure the coaxial connector thereto. As coaxial connectors of this type require a two-piece construction, including the body and the sleeve, often during shipping, handling and installation, the parts may become lost or misplaced.

U.S. Patent No. 4,834,675 addresses this problem by providing a coaxial connector where the locking sleeve is frangibly tethered to the connector body. Prior to installation, the locking sleeve is frangibly removed from the connector body whereupon the locking sleeve is inserted onto the cable and the cable is inserted into the connector body for securement thereto. While the connector of the '675 patent reduces the risk of mishandling or loss of the connector components during shipment, upon installation the locking sleeve must still be removed from the connector body and attached to the cable separately. Thus, there is still a risk of mishandling or loss of components during installation.

This problem is further addressed in U.S. Patent No. 5,470,257 where a coaxial connector is provided with a locking sleeve being inseparably coupled to a connector body. Cable termination using the connector of the '257 patent requires that the prepared coaxial cable be inserted axially through both the locking sleeve and connector body. Thereafter, the locking sleeve can be axially advanced so as to secure the cable in the connector body.

While in many installations, this form of cable termination is acceptable, it has been found that insertion of the prepared cable through both the locking sleeve and the connector body may be difficult in certain situations. As the cable installer typically works outdoors in an elevated or underground environment, it may become difficult to “blind” insert the prepared cable through the locking sleeve and into proper position around the cylindrical post of the connector body. In these situations, it would be desirable to permit the removal of the locking sleeve from the connector body so that the cable could be directly inserted into the connector body.

It is, therefore, desirable to provide a coaxial connector which supports the locking sleeve on the connector body, but which when circumstances require, permits the removal of the locking sleeve therefrom to permit ease of cable termination.

#### **SUMMARY OF THE INVENTION:**

It is an object of the present invention to provide a coaxial cable connector for terminating a coaxial cable.

It is a further object of the present invention to provide a coaxial cable connector having a connector body and a locking sleeve where the locking sleeve secures the cable within the connector body.

It is a further object of the present invention to provide a coaxial cable connector having a connector body and a locking sleeve in detachable, re-attachable snap engagement with the

connector body to permit direct insertion of the cable through the locking sleeve and the connector body. Alternatively, where circumstances require, the present invention permits removal of the locking sleeve from the connector body for subsequent separate reattachment.

5 It is another object of the present invention to provide a method of terminating a coaxial cable.

In the efficient attainment of these and other objects, the present invention provides a coaxial cable connector. The connector of the present invention includes a connector body having a cable receiving end and an opposed connection end. A locking sleeve is provided in detachable, re-attachable snap engagement with the insertion end of the connector body for securing the cable in the connector body. The locking sleeve is movable from a first position loosely retaining the cable in the connector body to a second position locking said cable to the connector body.

In a preferred embodiment of the present invention, the locking sleeve is in resilient detachable, re-attachable snap engagement with the connector body. The resilient detachable, re-attachable engagement is provided by cooperative detent structure between a portion of the sleeve insertable into the connector body and a portion of the connector body which receives the sleeve. This detent structure includes a rib and groove arrangement which provides for the detachable coupling of the sleeve to the connector body.

In a further preferred embodiment, the detachable engagement of the sleeve to the connector body may include one or more slots extending through the end of the sleeve which is inserted into the connector body. The slots facilitate resilient detachment and reattachment of the sleeve from the connector body.

5

In its method aspect, the present invention provides for the termination of a coaxial connector with a connector. The method provides for the detaching of a locking sleeve from a connector body. The sleeve is then positioned over the cable. The cable is then inserted into the end of the connector. The sleeve is then reattached to the end of the connector body to secure the cable thereto.

#### **BRIEF DESCRIPTION OF THE DRAWINGS:**

Figure 1 is an exploded perspective showing of the coaxial connector of the present invention including a connector body and a detachably coupled locking sleeve.

Figure 2 is a longitudinal sectional showing of the connector of Figure 1.

Figure 3 shows the connector of Figure 1 with the sleeve detachably coupled to the connector body.

Figures 4-6 are enlarged sectional showings of the engagement between the connector body and the locking sleeve.

Figure 7 is an exploded sectional showing of the termination of a prepared coaxial cable with the connector of the present invention.

#### **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS:**

5 The present invention is directed to connectors for terminating coaxial cable. Coaxial connectors of this type are shown and described in U.S. Patent No. 4,834,675 issued May 30, 1989, which is incorporated by reference herein for all purposes.

10 Referring to Figures 1-3, the coaxial cable connector 10 of the present invention is shown.

15 Connector 10 includes two major components, a connector body 12 and a locking sleeve 14 attachably coupled to body 12. Body 12 is an elongate generally cylindrical conductive member typically formed of metal, preferably brass. Body 12 includes an annular collar 16 for accommodating a coaxial cable, an annular nut 18 rotatably coupled to collar 16 for providing mechanical attachment of the connector to an external device. Interposed between collar 16 and nut 18 is an annular post 20. A resilient sealing O-ring 22 may be positioned between collar 16 and nut 18 at the rotatable juncture thereof to provide a seal thereat. Collar 16 includes a cable receiving end 24 for insertably receiving an inserted coaxial cable. Nut 18 includes an internally threaded end extent 26 permitting screw threaded attachment of body 12 to the external device. Cable receiving end 24 and internally threaded end extension 26 define the opposed ends of connector body 12. Annular post 20 includes a base portion 28 which provides for securement of post 20 between nut 18 and collar 16 and an annular tubular extension 30 extending into collar

18. As will be described in further detail hereinbelow and as is conventionally known, the extension 30 of post 20 and the collar 16 define an annular chamber 32 for accommodating the jacket and shield of the inserted coaxial cable.

5 Locking sleeve 14 is a generally cylindrical member formed of resilient material preferably a synthetic plastic such as an acetate resin. Locking sleeve 14 includes a flared rearward end 34 through which a cable may be inserted. Opposite rearward end 34 is a forward end 36 which is insertable into receiving end 24 of collar 16. As will be described in further detail hereinbelow, the forward end 36 of locking sleeve 14 and the receiving end 24 of collar 16 include cooperative detent structure which allows for the detachable, re-attachable connection of locking sleeve 14 to body 12. Furthermore, connector 10 is designed such that locking sleeve 14 is axially moveable along arrow A of Figure 3, towards nut 18 from a first position shown in Figure 4, which loosely retains the cable within connector body 12 through an intermediate position shown in Figure 5, to a more forward second position shown in Figure 6, which secures the cable within connector body 12.

The connector 10 of the present invention is constructed so as to be supplied in the assembled condition shown in Figure 3. In such assembled condition, and as will be described in further detail hereinbelow, a coaxial cable may be inserted through the rearward end 34 of locking sleeve 14 and through connector body 12. The locking sleeve may be moved from the first position loosely retaining the cable to the second position which is axially forward thereby locking the cable to the connector body. It is, however, contemplated that the locking sleeve 14 may be detached from connector body 12 and in a manner which will be described in further

detail hereinbelow, so as to allow the coaxial cable to be inserted directly into receiving end 24 of connector body 12. Thereafter, the locking sleeve 14 which has been placed around the cable may be reattached to receiving end 24 of body 12 where it can be moved from the first position to the second position locking the cable to the connector body.

5

The cooperating detent structure mentioned above, is employed to provide such detachment and reattachment of locking sleeve 14 to connector body 12. With additional reference to Figures 4-6, the cooperating detent structure is shown.

Receiving end 24 of collar 16 of connector body 12 includes a radially inwardly directed annular rib 40 extending adjacent the distal end thereof. Rib 40 is defined by a forwardly facing perpendicular wall 42 and a rearwardly facing chamfered wall 44.

The cooperating detent structure of the present invention further includes the forward end 36 of locking sleeve 14 formed to have a radially outwardly opening annular groove 46 adjacent a distal end thereof. Groove 46 is constructed so as to receive rib 40 of collar 16. Groove 40 is defined by a pair of spaced apart radially outwardly directed rings 48 and 50. Ring 48 which is axially forward of ring 50 is defined by opposed oppositely chamfered walls 48a and 48b. Similarly, ring 50 which is axially rearward, is defined by a pair of opposed oppositely chamfered walls 50a and 50b. As may be appreciated, the forward end 36 of locking sleeve 14 may be inserted into the receiving end 24 of collar 16. Upon insertion, the forward chamfered wall 48a of ring 48 bears against chamfered wall 44 of collar 16. Due to the resilient nature of



material forming locking sleeve 14, the ring 48 will ride over rib 40 and the rib 40 will become lockingly resident within groove 46. This defines the first position of locking sleeve 14.

While the locking sleeve is accommodated in collar 16 by engagement between the rib 40 in groove 46, locking sleeve 40 may be detachably removed from locking sleeve 14. Such detachable removal is facilitated by the resiliency of the plastic material forming locking sleeve 40 and relative thickness of the sleeve wall thereat. Furthermore, ring 48 includes rearward chamfered wall 48b which permits the wall to ride against perpendicular wall 42 of sleeve 16 upon rearward movement of locking sleeve 14. Such construction of the forward end 36 of sleeve 14 together with the formation of chamfered wall 48b and the resiliency and the thinness of the plastic material, allows the locking sleeve to be detachably coupled from the collar 16.

Furthermore, as particularly shown in Figures 1 and 4-6, the forward end 36 of the locking sleeve may include one or more axially extending slots 52 therethrough. The slots 52 are optionally included to enhance the resilient deflectability of the forward end 36 of locking sleeve 14. Where used, slots may be provided in any number desired to provide the degree of flexibility required to removably detach locking sleeve 14 from collar 16 without making the locking sleeve so deflectable that it inadvertently detaches from collar 16 during normal handling and shipment. Furthermore, the length of slots 52 may be selected to enhance the flexibility of forward end 36. As shown in Figures 4 and 5, a longer slot 52 may be provided as compared with a shorter slot shown in Figure 6.

It is further contemplated that while the locking sleeve is designed to be detachably coupled from collar 16 by moving sleeve 14 in a rearward direction with respect to collar 16, a slight transverse force in a direction of arrow B may be of assistance in detaching locking sleeve 14 from collar 16.

5

As more fully shown in Figures 6 and 7, the cooperative detent structure further includes a radially outwardly extending end ring 54 adjacent rearward end 34 of sleeve 14. Upon continued coaxial movement along arrow A, ring 54 engages and rides over rib 40 of collar 16 to define the second position which locks cable to connector body 12.

Having described the components of connector 10 in detail, the use of connector 10 in terminating a coaxial cable may now be described with respect to Figure 4-7.

Coaxial cable 60 includes an elongate inner conductor 62 formed of copper or similar conductive material. Extending around inner conductor 62 is a conductor insulator 64 formed of a suitably insulative plastic. A metallic shield 66 is positioned in surrounding relationship around insulator 64. As shown in Figure 5, shield 66 is a metallic braid, however, other conductive materials such as metallic foil may also be employed. Covering shield 66 is an outer insulative jacket 68.

20

Cable 60 is prepared in conventional fashion for termination, by stripping back jacket 68 exposing an extent of shield 66. A portion of insulator 64 extends therefrom with an extent of

conductor 62 extending from insulator 64. The preparation process includes folding back an end extent of shield 66 about jacket 68.

As shown in exploded view in Figure 7, cable 60 may be inserted into connector 10 with the locking sleeve 14 coupled to collar 16 of body 12 as shown in Figures 2 and 3. In this technique, the prepared cable 60 is inserted through rearward end 34 of sleeve 14 and into the receiving end 24 of collar 16. Extension 30 of post 20 of body 12 is inserted between the insulator 64 in the metallic shield 66 such that the shield and the jacket 68 reside within the annular region 32 defined between post 20 and collar 16. In this position, the locking sleeve is coupled to collar 16 in the first position shown in Figure 4. In such first position, sufficient clearance is provided between sleeve 14 and collar 16 so that extension 30 may easily be interposed between insulator 64 and shield 66.

Once the cable 60 is properly inserted, the locking sleeve 14 may be moved from the first position shown in Figure 4, to an intermediate position shown in Figure 5, where the locking sleeve is moved axially forward so that the rearward ring 50 rides over rib 40 so as to reside forward of perpendicular wall 42. Such movement is facilitated by the chamfered wall 44 of receiving end 24 of collar 16 and the forward chamfered wall 50a of ring 50. In this second position, the jacket 68 and shield 66 of cable 60 begins to become compressively clamped within annular region 32 between post 20 and collar 16. The sleeve 14 is further axially advanced along arrow A from the intermediate position shown in Figure 5, to a second position shown in Figure 6. Such second position is achieved as the end ring 54 resiliently rides over rib 40 of collar 16. In that regard, end ring 54 has a forwardly chamfered front wall 54a for engagement with

chamfered wall 44 of collar 16 to facilitate such resilient movement. Further, the rear wall 54b of ring 54 is perpendicular so as to engage perpendicular wall 42 of rib 40 to maintain sleeve 14 in the second position with respect to collar 16. A suitable tool may be used to effect movement of locking sleeve 14 from its first position to its second position securing cable 60 to connector  
5 body 12.

It is contemplated that the engagement between insulative jacket 68 and the connector body 12 establishes a sealed engagement thereat. In order to further facilitate the seal, locking sleeve 14 may optionally support a sealing O-ring 55 which provides a seal with the chamfered  
10 wall 44 of collar 16 in the second position.

As may be appreciated, proper insertion of cable 60 into connector body 12 requires that the cable be inserted in such a manner that the extension 30 of post 20 becomes resident between insulator 64 and shield 66. In certain installation settings, the installer may not have clear and  
15 convenient access when terminating cable 60. Moreover, insertion may be rendered difficult by poor cable preparation, which may result in a frayed end. Therefore, it may be difficult for the installer to blindly insert the cable 60 through the locking sleeve 14 and into connector body 12. In such situations, the present invention contemplates the ability to detachably remove locking sleeve 14 from connector body 12 so that the cable may be directly inserted to receiving end 24  
20 of collar 16. In these situations, locking sleeve 14 is detachably removed from collar 16 in a manner facilitated as above described. The locking sleeve is then slipped over cable 60 and moved to a convenient position along the cable length. The end of cable 60 may then be inserted directly into the rearward end 34 of collar 16 to easily assure that extension 30 of post 20 is

inserted between insulator 64 and shield 66. Thereafter, the locking sleeve 14 may be brought up along the cable and the forward end 36 of locking sleeve 14 may be inserted into the rearward end 34 of collar 16. The chamfered wall 48a of ring 48 together with the chamfered wall 44 of collar 16 and optionally the slots 52, facilitates insertion of the locking sleeve into collar 16 so that rib becomes resident within groove 46 as shown in Figure 4 defining the first position.

Thereafter, as described above, the locking sleeve may be moved from the first position shown in Figure 4 to a second position shown in Figure 6 where the end ring 54 becomes resident forward of perpendicular wall 42 thereby locking cable 60 in connector body 12.

Various changes to the foregoing described and shown structures will now be evident to those skilled in the art. Accordingly, the particularly disclosed scope of the invention is set forth in the following claims.